



# CITEL

## 2-pair Data surge protector unit

### B280-06D3



- 2-pair surge protection unit
- 6 V
- Removable protection circuit
- Wall mounting and screw connection
- UL497 A&B



Electrical Characteristics		
Network		RS422, RS485
Nominal line voltage	Un	6 Vdc
Max. DC operating voltage	Uc	8 Vdc
Max. frequency	f max.	20 MHz
Insertion loss		< 1 dB
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	20 kA
Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line)</i>	In	5 kA
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)</i>	Up	20 V
Impulse current <i>2 x 10/350μs Test - D1 Category</i>	Iimp	2.5 kA
Max. Load current	IL	300 mA
Line resistance		< 4.7 Ohm
Mechanical Characteristics		
Technology		GDT + R + Diode
SPD configuration		2 pairs
Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>
Format		Wall mounting box
Mounting		Wall mounting by screws (not supplied)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2
Spare module(s)		S280-06D3
Dimensions		See diagram
Weight		0.12 kg
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B
Certification		UL listed
Environmental standards		EU RoHS
Part number		
<b>72771</b>		

