




CITEL

Type 2 AC surge protector - 1-pole - pluggable

DAC50-10-660



- Type 2 AC multipolar surge protector
- In: 20 kA
- I_{max}: 50 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified



Electrical Characteristics

SPD type	IEC	2
Max. AC operating voltage	U _c	660 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	870 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	1150 Vac disconnection
Residual Current Leakage current to Ground	I _{pe}	< 1 mA
Follow current	I _f	None
Nominal discharge current 15 x 8/20 μ s impulses	I _n	20 kA
Max. discharge current max. withstand @ 8/20 μ s by pole	I _{max}	50 kA
Protection level @ I _n (8/20 μ s)	U _p	2.9 kV
Residual voltage at 5 kA @ 5 kA (8/20 μ s)	U _{p-5kA}	2.4 kV
Admissible short-circuit current	I _{sc}	50 000 A

Mechanical Characteristics

Technology		MOV
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm² (35mm² rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Ingress Protection rating		IP20 (NEMA 2)
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator - Red/Green
Spare module(s)		MDAC50-660
Remote signaling of disconnection		option DAC50S-10-660 : output on changeover contact
Dimensions		See diagram - 1TE (EN43880)

Disconnectors

Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG

Standards

Standards compliance	IEC 61643-11 / EN 61643-11
Certification	ÖVE

Part number

821110611

