





- ✦ Type 2 AC surge protector
- ✦ In: 20 kA
- ✦ I_{max}: 50 kA
- ✦ Pluggable module for each phase
- ✦ Remote signaling
- ✦ EN 61643-11, IEC 61643-11 compliance



V: High-energy varistor
 Ft: Thermal fuse
 C: Remote signal contact
 t*: Thermal disconnection system
 MI: Disconnection indicator

| Electrical Characteristics | | | |
|--|------------------------|--|--|
| SPD type | IEC | | 2 |
| Network | | | 120/208 V 3-phase |
| AC system | | | TNC |
| Max. AC operating voltage | U _c | | 150 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection | UT | | 180 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection | UT | | 230 Vac disconnection |
| Residual Current Leakage current to Ground | I _{pe} | | < 1 mA |
| Follow current | I _f | | None |
| Nominal discharge current 15 x 8/20 μs impulses | I _n | | 20 kA |
| Max. discharge current max. withstand @ 8/20 μs by pole | I _{max} | | 50 kA |
| Total Maximum discharge current max. total withstand @ 8/20 μs | I _{max} Total | | 150 kA |
| Protection mode(s) | | | L/PE |
| Protection level L/PE @ I _n (8/20 μs) | Up L/PE | | 1.2 kV |
| Admissible short-circuit current | I _{scr} | | 50 000 A |
| Mechanical Characteristics | | | |
| Technology | | | MOV |
| SPD configuration | | | 3-phase |
| Connection to Network | | | By screw terminals: 2.5-25mm ² |
| Format | | | Plug-in modular box |
| Mounting | | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | | Thermoplastic UL94 V-0 |
| Operating temperature | T _u | | -40/+85°C |
| Protection rating | | | IP20 |
| Failsafe mode | | | Disconnection from AC network |
| Disconnection indicator | | | 1 mechanical indicator by pole - Red/Green |
| Spare module(s) | | | MDAC50-150 |
| Remote signaling of disconnection | | | output on changeover contact |
| Wiring for remote signaling | | | 1.5 mm ² max. |
| Max. Voltage/Current for remote signaling | | | 250 V / 0.5 A (AC) / 30 V / 3 A (DC) |
| Dimensions | | | See diagram - 3 TE (EN43880) |
| Weight | | | 0.272 kg |
| Disconnectors | | | |
| Thermal disconnector | | | Internal |
| Installation ground fault breaker | | | Type 'S' or delayed |
| Back-up protection device | | | 50 A min. - 125 A max. - Fuses Type gG |
| Standards | | | |
| Standards compliance | | | IEC 61643-11 / EN 61643-11 |
| Certification | | | ÖVE / UL |
| Part number | | | |
| 821110123 | | | |