





- ✦ Type 2 AC surge protector
- ✦ In: 20 kA
- ✦ I_{max}: 50 kA
- ✦ Pluggable module for each phase
- ✦ Remote signaling
- ✦ EN 61643-11, IEC 61643-11 compliance



V: High-energy varistor
 Ft: Thermal fuse
 C: Remote signal contact
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics			
SPD type	IEC	2	
Network		600V 3-phase	
AC system		TNC	
Max. AC operating voltage	U _c	660 Vac	
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	870 Vac withstand	
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	1150 Vac disconnection	
Residual Current Leakage current to Ground	I _{pe}	< 1 mA	
Follow current	I _f	None	
Nominal discharge current 15 x 8/20 μs impulses	I _n	20 kA	
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	50 kA	
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total	150 kA	
Protection mode(s)		L/PE	
Protection level L/PE @ I _n (8/20μs)	U _p L/PE	2.9 kV	
Residual voltage L/PE at 5 kA @ 5 kA (8/20μs)	U _{p-5kA}	2.4 kV	
Admissible short-circuit current	I _{sc}	50 000 A	
Mechanical Characteristics			
Technology		MOV	
SPD configuration		3-phase	
Connection to Network		By screw terminals: 2.5-25mm ²	
Format		Plug-in modular box	
Mounting		Symmetrical rail 35 mm (EN 60715)	
Housing material		Thermoplastic UL94 V-0	
Operating temperature	T _u	-40/+85°C	
Protection rating		IP20	
Failsafe mode		Disconnection from AC network	
Disconnection indicator		1 mechanical indicator by pole - Red/Green	
Spare module(s)		MDAC50-660	
Remote signaling of disconnection		Output on changeover contact	
Wiring for remote signaling		1.5 mm ² max.	
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions		See diagram - 3 TE (EN43880)	
Disconnectors			
Thermal disconnector		Internal	
Installation ground fault breaker		Type 'S' or delayed	
Back-up protection device		50 A min. - 125 A max. - Fuses Type gG	
Standards			
Standards compliance		IEC 61643-11 / EN 61643-11	
Certification		ÖVE	
Part number			
821110623			