





#### 48VDC flashhead

- ✦ 6 led projectors in aluminium and glass
- ✦ 2 white led circuits and a red with infrared circuit inside each projector
- ✦ NVG visible
- ✦ Simple installation with no losing parts when opening the flash-head
- ✦ 48VDC led drivers inside a stainless enclosure located in flash-head
- ✦ Alarm activated in case of lamp default or power supply default
- ✦ Test button for day and night
- ✦ Luminous indicators for quick diagnostic
- ✦ 48Vdc surge protection with indicator showing when it has failed included
- ✦ GPS



Les dimensions sont en mm  
All dimensions are in mm



#### Electrical Characteristics

Average wattage	55W (day time), 8W (night mode)
-----------------	---------------------------------

#### Photometric Characteristics

Effective light output day time at 0° on site	20 000cd (white)
Effective light output twilight mode at 0° on site	20 000cd (white)
Effective light output night mode at 0° on site	2000cd (red) with IR
Color day/twilight time	white
Color night time	Red or white

Vertical beam spread	3°
----------------------	----

Horizontal beam spread	360°
------------------------	------

Flash per minute	40
------------------	----

#### Mechanical Characteristics

IP degree	IP66 per projector
Wiring	Entry of cable by glands nickel plated brass and connection by terminals
Operating temperature	Tu -40/+55°C
Weight	14kg
Size of the light	333mm (height) x 500mm (diameter)
Cable entry diameter	11 to 21mm
Wire cross section	from 1 to 4 mm <sup>2</sup>
Attachment	6 mounting holes dia.16mm, dia.337mm circle (FAA standard)

#### Standards

Standards compliance	ICAO annexe 14 chapter 6 (8th edition 07/2018), EASA (4th edition 2017)
----------------------	---

#### Part number

113792