





#### 48VDC flashhead

- ✦ 6 led projectors in aluminium and glass
- ✦ 2 white led circuits and a red with infrared circuit inside each projector
- ✦ NVG visible
- ✦ Simple installation with no losing parts when opening the flash-head
- ✦ 48VDC led drivers inside a stainless enclosure located in flash-head
- ✦ Alarm activated in case of lamp default or power supply default
- ✦ Test button for day and night
- ✦ Luminous indicators for quick diagnostic
- ✦ 48Vdc surge protection with indicator showing when it has failed included
- ✦ GPS



Les dimensions sont en mm  
All dimensions are in mm



#### Características eléctricas

Average wattage 55W (day time), 8W (night mode)

#### Características fotométricas

Effective light output day time at 0° on site 20 000cd (white)

Effective light output twilight mode at 0° on site 20 000cd (white)

Effective light output night mode at 0° on site 2000cd (red) with IR

Color day/twilight time white

Color night time Red or white

Vertical beam spread 3°

Horizontal beam spread 360°

Flash per minute 40

#### Características mecánicas

IP degree IP66 per projector

Wiring

Entry of cable by glands nickel plated brass and connection by terminals

Temperatura de operación Tu

-40/+55°C

Size of the light

333mm (height) x 500mm (diameter)

Weight

14kg

Cable entry diameter

11 to 21mm

Wire cross section

from 1 to 4 mm<sup>2</sup>

Attachment

6 mounting holes dia.16mm, dia.337mm circle (FAA standard)

#### Normas

Conformidad con las normas

ICAO annexe 14 chapter 6 (8th edition 07/2018), EASA (4th edition 2017)

#### Código

113792