





CITEL

1-pair DIN rail plug-in Data surge protector

DLA-48DBC



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode

Electrical Characteristics		
Network	Fipway, WorldFIP, FieldBus-h2	
Nominal line voltage	Un	48 V
Max. DC operating voltage	Uc	53 Vdc
Max. frequency	f max.	20 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	300 mA
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	20 kA
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	75 V
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	75 V
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA
Nominal discharge current C2 Category	I _n	5 kA
Line resistance (± 10%)		4.7 Ohm
Mechanical Characteristics		
Technology	GDT+TVS diode	
SPD configuration	1-pair+shielded	
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²	
Format	Plug-in DIN box	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Failsafe mode	Short-circuit	
Disconnection indicator	Transmission interrupt - default mode 2	
Spare module(s)	DLAM-48DBC	
Dimensions	See diagram	
Standards		
Standards compliance	IEC 61643-21 / EN 61643-21	
Part number	640421	

