



# CITEL



## 19" patch panel surge protector for high-speed network

### RAK32-E-C6-S0

- ▶ 19" patch panel surge protector for CAT6
- ▶ 32 ports
- ▶ In/Out front : RJ45
- ▶ Maintenance possible per port
- ▶ Secondary protection
- ▶ UL497B



Electrical Characteristics		
Network		100/1000/10G BaseT, RS422, RS485, RS423, Ethernet
Nominal line voltage	Un	5 Vdc
Max. DC operating voltage	Uc	7.5 Vdc
Max. frequency	f max.	250 MHz
Max. data rate		10 Gbps
Insertion loss		< 1 dB
Max. load current @25°C	IL	750 mA
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	500 A
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-Y (Line/Line)	Up	20 V
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-C (Line/Earth)	Up	20 V
Max. capacitance	C	< 8 pF
Discharge current at 10/1000µs impulse current		100 A
Line/Line Nominal discharge current C2 Category	In L/L	500 A
Mechanical Characteristics		
Technology		Diode écrêtage
SPD configuration		32 ports of 8 wires
Connection to Network		RJ45 Female input/output
Format		Rack 19"
Mounting		19" rack or wall
Housing material		Aluminium
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt
Spare module(s)		1-port removable circuit
Remote signaling of disconnection		No
Pinout		(1-2)(3-6)(4-5)(7-8)
Dimensions		See diagram
Weight		0.1 kg
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B / IEEE 802-3an
Part number		
6257		

